



# Product Data Sheet

[www.calumetspecialty.com](http://www.calumetspecialty.com)

If you have questions regarding this product, please contact your Sales Representative. Customer Service and Technical Service can be reached at 1-800-437-3188.

<b>Name</b>	<b>Product Code</b>	<b>Revised</b>
Duoprime® Oil 90	L6200-00-H	12/04/2009

**STCC** 29-114-25

**HazMat Name** Non-Regulated

Test	Method	MIN	MAX	Typical
Viscosity, CST @ 40C	D445	14.2	16.5	15.6
Viscosity, CST @ 100F	D445	15.4	17.9	16.9
Viscosity, SUS @ 100F	D2161	79.0	89.0	85.1
Gravity, API, 60°F	D4052	30.8	37.0	33.2
Specific Gravity @ 25/25 C	D4052	0.834	0.866	0.853
Flash, COC, C(F)	D92	177(350)		191(375)
Pour Point, C(F)	D97		-12(10)	-27(-16)
Color (Saybolt)	D156	+30		+30
Carbonizable Substances	D565	PASS		PASS
Solid Paraffins	USP	PASS		PASS
Water	ARCO 8033			PASS
Appearance	ARCO 8039	BRIGHT		BRIGHT
Acidity	USP	PASS		PASS
UV Absorbance (FDA 21 CFR 172.878)	D2269	PASS		PASS
Limit of Polycyclic Aromatic Hydrocarbons	USP	PASS		PASS
Limit of Sulfur Compounds	USP	PASS		PASS
Infrared Absorption	USP	PASS		PASS
This Material is an NF Mineral Oil				

Copyright 2008 Calumet Specialty Products Partners, L.P.

Calumet's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. Typical values only represent the values one would expect if the property were tested in our laboratories with our test methods on the specified date. Some product properties are not frequently measured, and accordingly typical values are not based on a statistically relevant number of tests. The information in this document relates only to the named product. The user is solely responsible for all determination regarding any use and any process.