

**MATERIAL SAFETY DATA SHEETS**

Trade Name: **COAST TFD 30 AND 50**

Commodity Code: MG1040  
Synonyms: Lubricating Oil

Date: September 25, 2000  
Technical Contact: Coast Oil Company  
Safety Director: (408)252-7720  
Chemtrec Emergency: (800)424-9300

CAS NO.: Mixture  
(Refer to Section 1.0)

---

**MATERIAL HAZARD EVALUATION**

(Per OSHA Hazard Communication  
Standard [29 CFR Part 1910.1200]) (OHCS)

Health: Final Product Non-Hazardous. Possible Minor Allergen.

Precautionary Statement: Avoid prolonged skin contact.

HMIS Rating<sup>1</sup>: Health 1 Flammability 1 Reactivity 0

**1.0 Generic Composition/Components**

<u>Components</u>	<u>CAS #</u>	<u>%</u>	<u>Hazard Data</u>
Refined Petroleum Oil(s)	64742-58-1	90 - 94	Oral: LD50 (rat): 5000ng/KG Eye: Practically Non-Irritating Skin: Practically Non-Irritating

Proprietary Components: Mixture 6-10  
Antiwear, rust and oxidizing  
inhibitors may contain zinc  
Phosphorus, sulfur, and calcium

Eye: Minor irritant  
Dermal: Minor irritant

Oil mist if generated.

Contains mineral oil observe the Osha  
PEL of 5 mg per cubic meter,  
ACGHSTEL, of 10mg. per cubic meter.

---

<sup>1</sup> Hazard Rating: Least-0; Slight-1; Moderate-2; High-3; Extreme-4

## 2.0 Physical Data

Comment [DS1]: Page: 2

Physical Hazard Classification (Per 29 CFR Part 1910.1200)

Yes	Combustible	No	Flammable	No	Pyrophoric
No	Compressed Gas	No	Organic Peroxide	No	Reactivity
No	Explosive	No	Oxidizer	Yes	Stable

API Gravity: 23.9-25 API @ 60°F  
Pour Point: -12°C  
Specific Gravity (60/60°F) (H<sub>2</sub>O. = 1): .90-.91  
% Volatiles by Volume: Negligible  
Melting Point, °C (°F): NA  
Vapor Pressure, mmHg (20°C): ~<0.001 mmHg  
Solubility in H<sub>2</sub>O., % by Weight: Insoluble  
pH of Undiluted Product: ND  
Appearance and Odor: Amber liquid, No odor.  
Density: 7.1 lb/gal

How To Detect This Substance: Viscous only.  
Amber colored liquid with a characteristic  
petroleum odor and slippery feel.

## 3.0 Fire and Explosion Data

Flash Point, COC, °F (°C)	430° (221°)
Fire Point, CC, °F (°C)	450° (232)
NFPA Rating <sup>4</sup>	Health: 1 Flammability: 1 Reactivity: 0
Flammable Limits (% by volume in air)	Lower: 1% volume (mist) Upper: 10% volume (mist)
Extinguishing Media	Carbon dioxide, foam, dry chemical
Special Fire Fighting Procedure	None.
Unusual Fire or Explosion Hazard	Material may burn, but not ignite readily

## 4.0 Reactivity Data

Stability: Stable  
Conditions Contributing to Instability: None  
Incompatibility: Strong oxidants  
Hazardous Decomposition Products: Thermal decomposition in the presence of air  
may yield major amounts of oxides of carbon  
and minor amounts of oxides of sulfur and  
nitrogen.  
Conditions Contributing to Hazardous  
Polymerization: None

<sup>4</sup> Hazard rating: Least-0, Slight-1, Moderate-2, High-3, Extreme-4

*Unusual Fire and Explosion Hazards:* Move container from fire area if you can do so without risk. Apply cooling water to sides of containers that are exposed to flames until well after fire is out. Stay away from ends of tanks and drums--Heated containers may rupture, explode or be thrown into the air. Heated vapors may be sensitive to static discharge, resulting in fire or explosion.

*Fire Fighting Procedures:* Withdraw immediately in case of rising sound from venting safety device or discoloration of tank due to fire. Keep storage containers cool with water spray. Use self-contained breathing apparatus (SCBA).

NFPA Rating (0=least, 4=extreme): Health = 1 Fire = 1 Reactivity = 0

## 5.0 Spill or Leak Procedures

### Procedures if Material is Spilled:

- Remove sources of heat or ignition, provide adequate ventilation, contain leak for possible re-refining.
- **Small Spills:** Absorb with suitable material such as rags, clay absorbent, or sand. Place into containers for later removal.
- **Large Spills:** Contain spill in earthen dikes for later recovery.
- Report spills as required to appropriate authorities.

### Waste Disposal:

- It is the responsibility of the user to determine if the material is hazardous waste at the time of disposal.
- Check before disposing to be sure you are in compliance with all applicable laws and regulations.
- Chemtrec/RCRA Emergency Hotline Number: 800-424-9300.

### Protective Measures During Repair and Maintenance of Contaminated Equipment:

- Refer to Section VII - Special Protection Information.
- Wash exposed skin thoroughly with soap and water.
- Avoid prolonged contact with used oil.
- Remove soiled clothing.
- Use oil impervious gloves if frequent or prolonged contact is expected.

## 6.0 Health Hazard Data

### Health Hazard Classification

(Per 29 CFR Part 1910.1200)

No	Carcinogen	No	Corrosive
No	Animal Carcinogen	No	Irritant
No	Suspect Carcinogen	No	Sensitizer
No	Mutagen	No	Teratogen
No	Highly Toxic	No	Target Organ
No	Toxic		

Product listed as Carcinogen or Potential Carcinogen by:

NTP No IARC No OSHA No Other No

**Toxicity Summary:** Practically non-toxic, except for minor allergenic potential.

**Major Route(s) of Entry:** Inhalation of incidental mists or vapors.

#### Acute Exposure Symptoms

**Inhalation:** Low risk of inhalation at ambient temperatures. Mists or fumes may cause drowsiness, dizziness, headache, nausea, or lung irritation or chemical pneumonitis. High concentrations of vapor or mist may be irritating to the respiratory tract. Including nose and throat, may cause difficulty breathing.

**Dermal Contact:** Transient, slight irritant, possible mild allergen. Prolonged or repeated contact may cause redness, burning and dermatitis. Contact with hot material may cause thermal burns.

**Eye Contact:** May be mildly irritating. Direct contact may cause burning, tearing and redness. Contact with hot material may cause thermal burns.

**Ingestion:** Low toxicity. At a Saybolt viscosity of 170 SUS (100°F), the risk of aspiration into the lungs is reduced. If less than 1 oz. is ingested, material may pass through the system without harm. On ingestion of large quantities, slight GI discomfort, diarrhea, and headache may occur. Aspiration into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death. Human lethal dose - 1 pint.

**Injection:** Subcutaneous or intramuscular injection may cause irritation, erythema, edema.

#### Chronic Exposure

Prolonged and/or frequent contact may cause drying, cracking (dermatitis) or folliculitis. High oil mist concentrations may lead to oil pneumonia.

#### Other Special Effects

None.

---

**Medical Conditions Aggravated by Exposure**

Contact with skin may aggravate pre-existing dermatitis.

**First Aid and Emergency Procedures for Acute Effect**

- Inhalation:** Remove to fresh air. Respiratory support if necessary, should be administered by qualified personnel. Do not leave victim unattended. Seek medical attention if necessary.
- Dermal:** Do not use gasoline's, thinners or solvents to remove product from skin. Wipe material from skin and remove contaminated clothing. Wash with soap and water, and if necessary a waterless skin cleaner. Do not wear heavily contaminated clothing before laundering.
- Eyes:** Flush with water for 15 minutes lifting upper and lower lids occasionally. See physician if any complications arise.
- Ingestion:** Do not induce vomiting, because material can enter the lungs and cause severe damage. Drink 4 to 8 ounces of water and seek immediate medical attention. Do not leave victim unattended. If vomiting occurs, or if comatose or lethargic, place on the left side with the head down, seek immediate medical attention.
- Injection:** Subcutaneous injection is medical emergency. Seek medical aid immediately.

**Notes to Physician:** Following ingestion, at a Saybolt viscosity of ~170 SUS @ 100°F, the risk of aspiration into the lungs is reduced. For quantities above 1 oz., emesis or lavage may be considered. Subcutaneous or intramuscular injection requires prompt surgical debridement. If not familiar with technique, seek skilled advise.

**7.0 Special Protection Information**

**Ventilation Requirements:** Use in well ventilated area. In confined space, mechanical ventilation may be required to keep levels of certain components below mandated standards, as evaluated by designated personnel. Keep away from heat, sparks and flames.

NA - Not Applicable                      ND - No Data                      NE - Not Established

**Permitted Threshold Air Concentrations:**

Petroleum Hydrocarbon Mist	TLV-TWA	5mg/m <sup>3</sup>	OSHA-PEL	5/mg/m <sup>3</sup>
	TLV-STEL	10mg/m <sup>3</sup>	OSHA-STEL	ND
	TLV-Ceiling	ND	OSHA-Ceiling	ND
			OSHA-Peak	ND

**Specific Personal Protective Equipment:**

**Respiratory:** Normally none required. If high vapor or mist concentrations expected - use respirator approved for organic vapors and mists.

**Eyes:** Avoid contact with eyes. Safety goggles, or chemical splash goggles if splashing is anticipated. Contact lenses should not be worn.

**Dermal:** Oil impervious gloves if frequent or prolonged contact is expected. Barrier creams that are specific for oil based materials are recommended when gloves are impractical.

**Other Clothing or Equipment:** Wear body-covering work clothes to avoid prolonged or repeated exposure. Launder soiled work clothes before reuse. It is suggested that a source of clean water be available in work area for flushing eyes and skin.

## 8.0 Transportation and Special Precautions

**Storage:** Do not apply high heat or flame to container. Keep separate from strong oxidizing agents. Keep container tightly closed.

**Caution:** Empty containers may contain product residue which could include flammable or explosive vapors.

Consult appropriate Federal, State and Local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers and/or waste residues of this product.

### DOT Information

DOT/UN Shipping Name:	Petroleum Lubricating Oil
DOT Hazard Class:	Non-Hazardous
DOT/UN Hazard Identification Number:	None Assigned
DOT Shipping Container Restrictions:	None
DOT Placard:	None
CHRIS Code:	ND
Compatibility Category:	ND

## 9.0 Environmental Data

Product Name	TFD 30 AND 50
Commodity Code:	COAST

---

## SARA TITLE III

### Section 313 - Toxic Chemicals

This product does not contain Greater than 1.0% (greater than 0.1% for carcinogenic substance) of any chemical substances listed under SARA section 313.

### HAZARDES INGREDINENT

This material has no known hazards under applicable law.

**Clean Water Act**

Under Section 311 (b) of the Clean Water Act, discharges of crude oil and petroleum products in any kind or form to surface waters must be immediately reported to the National Response Center: 800-424-8802.

**Comprehensive Environmental, Response, Compensation and Liability Act (CERCLA) - Section 102 Hazardous Substances**

<u>Component</u>	<u>CAS #</u>	<u>%</u>	<u>RQ lbs.</u>
------------------	--------------	----------	----------------

Petroleum and petroleum fractions are excluded from the list of CERCLA hazardous substances by Section 101(14) of CERCLA.

**California Prop 65**

This product may contain chemicals known to the State of California to cause cancer. And/or birth defects based on maximum impurity levels of componets.

<1PPM BENZENE, GAS NO. 71-43-2  
<1PPM CADMIUM  
<1PPM ETHYLENE OXIDE, CAS NO. 75-21-8  
<1PPM LEAD  
<1PPM ARSENIC  
<1PPM ETHYL OXYLATE GAS NO. 140-895

**10.0 Labeling**

NOTE

*Prevent direct dermal contact with material.  
May have mild allergenic potential.*

---

ALL STATEMENTS, INFORMATION, AND DATA PROVIDED IN THIS MATERIAL SAFETY DATA SHEET ARE BELIEVED TO BE ACCURATE AND RELIABLE, BUT ARE PRESENTED WITHOUT GUARANTEE, REPRESENTATION, WARRANTY, OR RESPONSIBILITY OF ANY KIND, EXPRESSED OR IMPLIED. ANY AND ALL REPRESENTATIONS AND/OR WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFICALLY DISCLAIMED. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE. NOTHING CONTAINED HEREIN IS INTENDED AS PERMISSION, INDUCEMENT, OR RECOMMENDATION TO VIOLATE ANY LAWS OR TO PRACTICE ANY INVENTION COVERED BY EXISTING PATENTS, COPYRIGHTS OR INVENTIONS.

NA - Not Applicable  
mg1040.DOC

ND - No Data

NE - Not Established