



Soluble Oil

Soluble Oil is a chlorine-free, light-duty metalworking fluid developed to emulsify easily and form a stable emulsion when mixed with water. It provides excellent cooling and lubricity for light-duty cutting and grinding of ferrous and non-ferrous metals, resulting in extended tool life and good surface finishes on the machined parts.

Soluble Oil is formulated with naphthenic base oils and fortified with emulsifiers that form a stable emulsion when mixed with water. The high specific heat of water and the excellent metal wetting ability of the emulsion provide excellent cooling and lubricity for grinding, cutting and other machining operations. This promotes longer tool life by reducing friction between the cutting tool and the workpiece and by dissipating heat.

Soluble Oil provides good rust protection for both the cutting tool and the parts being machined. It has very low foaming tendency, which is an advantage in high-speed machining and grinding operations.

Note: Soluble Oil does not contain a biocide. A biocide such as Bioban™ P-1487 or Bioban™ GK should be added in service to combat the growth of harmful microorganisms in machine sumps and reservoirs.

Applications

Soluble Oil is recommended for light-duty machining operations with water hardness up to 250 ppm. Typical applications include:

- Broaching
- Drilling
- Grinding
- Milling
- Sawing
- Tapping

Features/Benefits

- Excellent cooling and lubricating properties
- Helps extend cutting tool life
- Reduces grinding wheel wear
- Good surface finish
- Emulsifies easily with water⁽¹⁾
- Forms a stable emulsion
- Good rust protection
- Good antifoam properties

**Emulsifiable
Metalworking Fluid**

Contact Information

**U.S. Customer
Service:
1-800-822-6457**

**U.S. Technical
Services Hot Line:
1-800-766-0050**

**International:
+1-832-486-3363**

**E-mail address:
lubricants@
conocophillips.com**

<http://lubricants.conocophillips.com>

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



⁽¹⁾ **Note:** When mixing, always add Soluble Oil to water; **never** add water to Soluble Oil. Typical concentrations (Soluble Oil in water) range from 3% to 10% for cutting operations and from 3% to 4% for grinding operations, depending on the type of metal and water hardness. Concentration may be monitored with a refractometer.

CAUTION: Containers of Soluble Oil should be stored indoors. They should **not** be stored at temperatures below 40°F (4°C) or above 130°F (54°C). Under proper storage conditions, the shelf life of Soluble Oil is one year. After one year, the product should be disposed of properly and not used.

Soluble Oil

Typical Properties

ISO Grade	32
Density, g/cm ³ @ 15.6°C (60°F)	0.917
Density, lbs/gal @ 15.6°C (60°F)	7.64
Color, ASTM D1500	3.0
Flash Point (COC), °C (°F)	177 (351)
Pour Point, °C (°F)	-20 (-4)
Viscosity,	
cSt @ 40°C	28.5
cSt @ 100°C	6.0
SUS @ 100°F	146
SUS @ 210°F	46
Viscosity Index	162
Emulsion Stability	Good
Foam Test, ASTM D892	Pass
pH, 5% (1:20) dilution	9.6
Rust Test, ASTM D665 A&B	Pass
Chlorine, wt %	Nil
Fatty Oil, wt %	Nil
Sulfur, Total, wt %	0.28
Sulfur, Active, wt %	Nil

Due to continual product research and development, the information contained herein is subject to change without notification.

Copyright © 2006 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.

**CONOCO****Recommended Concentrations, Soluble Oil in Water (Volume %)**

Operation	High Alloy Steels	Tool Steels	Nickel Alloys
Broaching, Milling, Tapping	10	10	10
Deep Drilling, Gear Hobbing, Gear Shaping, Sawing	5	7	7
Grinding	3	3	3

Refractometer Reading

Dilution Ratio	1:10	1:15	1:20	1:25	1:30
Reading	10.3	7.2	5.4	4.6	3.0

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Due to continual product research and development, the information contained herein is subject to change without notification.

Copyright © 2006 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.