



4250 Williams Road, San Jose, California 95129-3344  
Office: 408-252-7720 Plant: 408-251-0810  
Developers and Manufacturers of Fine Petroleum Products Since 1935



## PRODUCT INFORMATION

### COAST Ultra SPECIAL 15w-40

Coast Ultra Special 15w-40 is a recycled re-refined formulated all-season heavy duty motor oil for off highway diesel, highway diesel and mixed gasoline diesel powered fleets prior to 2001. Coast Ultra Special 15w-40 is not recommended for use in engines with emission gas recirculation (EGR) valves. Coast Ultra Special 15w-40 provides, deposit and consumption control, oxidative stability, fuel efficiency, icy for older mixed fleet operations at a reasonable cost.

#### TYPICAL TEST DATA

SAE GRADE	15W-40
APPEARANCE	Straw
GRAVITY API	28.5
FLASH COC, °F(°C)	410(210)
POUR PT, °F °C	-5(-20)
TBN	8
VISCOSITY CP AT 15C°	3200
CST AT 100C°	14.3
CST AT 40C°	100.0
SUS AT 100F°	475
SUS AT 210F°	76
VISCOSITY INDEX	147
SULFATED ASH WT% BELOW	1
Recycled re-refined	74%

**APPLICATIONS:** Formulated to meet or exceed industry requirements for older vehicles

**SAE 15W-40 - API SERVICE CLASSIFICATION CF, CF-2, CF-4, CG-4, CH-4-SJ**

**Major Diesel Engine Requirements:**

Mack EO-M, Cummins CES 20076/20071, Volvo VDS, Detroit Diesel.

**DISPOSAL:** Used oil must be handled with caution and should be sent for recycling.

**MATERIAL SAFETY DATA SHEETS AVAILABLE BY CALLING: 408-252-7720 or [www.coastoil.com](http://www.coastoil.com)**