



4250 Williams Road, San Jose, California 95129-3344
Office: 408-252-7720 Plant: 408-251-0810
Developers and Manufacturers of Fine Petroleum Products Since 1935



PRODUCT INFORMATION

COAST SUPREME 5W-20

Coast Supreme 5W-20 is a premium quality crankcase lubricate blended from high quality hydro cracked high viscosity index base oils with GF-3 energy conserving additives. Coast 5W-20 motor oil using the latest high quality base stocks and GF-4 additive package is formulated to meet the performance requirements of ILSAC GF-4 and API SM.

TYPICAL TEST DATA

| | |
|---------------------------|---------|
| SAE GRADE | 5W-20 |
| APPEARANCE | STRAW |
| GRAVITY API | 32.5 |
| FLASH PT(PMCC), °F | <170 |
| POUR PT, °F | -45 |
| TBN | 7.3 |
| VISCOSITY CP At - 35C° | 6000 |
| CST AT 100C° | 8.8 |
| CST AT 40C° | 52 |
| SUS AT 100C° | 254 |
| SUS AT 210C° | 60.1 |
| Volatility | |
| D5800 | 15% MAX |
| D6417 | 10% MAX |

APPLICATIONS: Coast Supreme 5W-20 motor oil be recommended for the following:
ILSAC GF-4, GF-3, GF-2 and GF-1 Oils are required.

API SM, SL, SJ, SH, SG, SF and SE oils are required- Energy Conserving
Ford M2C-153H/G/F/E oils are required.

All gasoline engine requiring SAE 5W-20 viscosity motor oils including many of the new Honda, Ford, and Madza autos.

DISPOSAL: Used oil must be handled with caution and should be sent for recycling.

Products not recommended for two cycle and aircraft gasoline engine.

MATERIAL SAFETY DATA SHEETS AVAILABLE BY CALLING: 408-252-7720