



4250 Williams Road, San Jose, California 95129-3344
Office: 408-252-7720 Plant: 408-251-0810
Developers and Manufacturers of Fine Petroleum Products Since 1935



PRODUCT INFORMATION

COAST TFD FLUID

Coast TFD Fluid is formulated to perform at higher operating temperatures. The product provides improved friction and anti-wear performance compared to TO-2 fluids. Coast TFD Fluid should be used whenever a product meeting the Caterpillar TO-4 specification is required. SAE 30 grade can be used in applications requiring an Allison C-4 product.

TYPICAL TEST DATA

SAE OR GRADE	30	50
APPEARANCE	Pale	Dark Pale
GRAVITY API	25.6	24.3
FLASH COC, °F	450	470
POUR PT, °C	-10	-17.8
VISCOSITY		
SUS AT 100°F	530	1220
SUS AT 210°F	62	95.9
CST AT 40°C	100.1	231
CST, AT 100°C	10.9	18.9
VISCOSITY INDEX	93	92

APPLICATIONS: Meets requirements of the Caterpillar TO-4 specification. SAE 30 grade recommended for Allison C-4 applications. Recommended for Komatso Dresser construction equipment.

Coast TFD Fluid cannot be used in farm tractors or other applications where wet brakes and clutches are used. Updated 4.18.07.

Disposal: used oil must be handled with caution and should be sent for recycling.

MATERIAL SAFETY DATA SHEETS AVAILABLE BY CALLING: 408-252-7720 or www.coastoil.com