



4250 Williams Road, San Jose, California 95129-3344  
Office: 408-252-7720 Plant: 408-251-0810  
Developers and Manufacturers of Fine Petroleum Products Since 1935



## PRODUCT INFORMATION

### Coast Ultra 400 Low Emission 15W-40

Coast Ultra 400 Low Emission 15W-40 is a high performance engine oil formulated for use in today's new low emission ULSD engines. It is also fully compatible with previous API service categories and engine models Coast Ultra 400 Low Emission 15W-40 is formulated to protect exhaust after treatment devices such as diesel particulate filters (DPFs) and diesel oxidation catalysts (DOLS). The additives provide superior soot dispersancy, thermal and oxidative stability, corrosion and value train- wear protection, and will prevent the formation and accumulation of deposits and sludge. Premier quality re-refine oils are used to meet the demanding requirements for heavy duty diesel and modern day gasoline engines.

#### TYPICAL TEST DATA

SAE GRADE	15W-40
APPEARANCE	Pale
GRAVITY API	28.5
FLASH COC, °F(°C)	204 (399)
POUR PT, °F °C	-30 (-22)
TBN	7.3
VISCOSITY @ 40C, st	119
VISCOSITY @100C, st	15.2
SULFANATED ASH, D874, WT%	.835
PHOSPHORUS, WT%	0.11
ZINC, WT%	0.12
% RECYCLED RE- REFINED	72

**APPLICATIONS:** Coast Ultra 400 Low Emission 15W-40 is for use in passenger cars, trucks and heavy equipment where the manufacturer recommends and API CJ-4/ SM performance rating.

#### **MAJOR DIESEL ENGINE REQUIREMENT:**

**API:** CJ-4, CI-4 Plus, CH-4, SM, SL, SJ

ACEA E-7, CATERPILLAR EFC-3, CUMMINS CES 20081, Mercedes Benz 228.1, 228.3, DETROIT DIESEL POWER GUARD 93K218, 93K214, 7SE270, MACK EO-N PP07, VOLVO VDS-4, VDS-3.

**DISPOSAL:** Used oil must be handled with caution and should be sent for recycling.

**MATERIAL SAFETY DATA SHEETS AVAILABLE BY CALLING: 408-252-7720**